





Happier Living Everyday



















Download BPL Promise App to experience the latest in









- Alphanumeric LCD Display (20X4 Characters) User Configurable Anatomical Programming
 155 Anatomical Programs
- Pre-Set Key for instant selection
- Self-Diagnostic Program X-Ray Counter with password protection
 Memory to retain last selected factors • 40 to 100 kVp in steps of 2 kVp only



Counter Balanced Tube Head with Vertical, Horizontal, Rotational,



Durable wheels & Efficient Foot Brake mechanism






monitoring input line Voltage & independent Ammeter for indication of Tube Current





BPL MRAD™ Technical Specifications 8 kW as per ISI (IS: 7620-Part-I). Generator Output

mA	100 mA
mAs Range	Upto 200
kVp RANGE	40 to 100 kVp in Steps of 2 kVP/Step
Digital Display	kV, mA & mAs
X-Ray Tube Type	Stationary Anode
Focal Spot	2.8 mm²
Collimator	Manually Operated with Light Beam Diaphragm
Collimator ON/OFF	From Control Panel
Control Panel	Digital Control Panel with Alphnumeric LCD
Anatomical Programming	155 Programs
	Memory to retain last selected factor
Other Features	Pre-Set factors
	Self Diagnostic Programming
Stand	Counter balanced Mobile Stand
Hand Switch	Dual action
Power Supply	230 V(±10%) AC 50 Hz, Single Phase,15 Amps, Line Resitance of < 0.4 Ohms



CERTIFIED ISO 13485:2003, ISO 9001:2008 COMPANY

11th KM, Bannerghatta Road, Arakere, Bangalore - 560076 CIN: U33110KA2012PTC067282 Ph: +91 80 26484388/ 2648 4350 Toll Free: 1800-4252355 We bsite: www.bpl medical technologies.comFor Enquiries: sales.medical@bpl.in

BPL Medical Technologies Private Limited



